

D LAB DM0506 low-speed centrifuge, supplied with built in fixed angle rotor A6-15P which can hold up to 15mL/10mL/7mL/5mLx6 tubes. It is widely used for blood or urine separation in medical routine practice in hospitals, clinics or research institutes.

## DM0506 Low-speed Centrifuge



### Features

- Speed range from 300-5000rpm;
- Rotor speed can be set and displayed by RPM or G-force;
- Two programs P1/P2 can be stored for routine practice;
- Rotor capacity for 15mL/10mL/7mL/5mLx6 tubes;
- Easy-to-read processing display and sound alert;
- Automatic lid-lock release after running;
- Maintenance-free brushless DC motor.



### Specifications

#### DM0506

Speed Range	300-5000rpm, increment:10rpm
Max. RCF	2350xg, increment: 10g
Speed accuracy	±20rpm
Rotor capacity	6x15mL/10mL/7mL/5mL
Run Time	30sec-99min, HD (continuous running)
Motor	Brushless DC motor
Display	LCD
Programs Memory	2
Safety Devices	Door interlock, Overspeed detector, Automatic internal diagnosis
Acceleration/Deceleration	1 ↑ 2 ↓
Power	Single-phase, 100V-240V,50Hz/60Hz, 70W
Dimension (WxDxH)	300X240X180mm
Weight	5.2kg
Advanced features	Speed/RCF switch; sound-alert function

